

OPTICAL RECEIVER [OR4x-x]


Fiber Products, Receivers

Features

- Headend 19 in. Rack Mount Enclosure
- Supports 4 Optical Receiver Modules
- LED Status Monitor Indicators for Each Module
- RF Test Point Provided on Back Panel
- RF Output Level can be Adjusted
- Adjustable Attenuator Located on Front Panel
- Power of 135 ~ 250 VAC
- Weight of 3kg / 7lbs
- Dimensions (LxWxH) of 483. x 385 x 44 mm (19 x 15 x 1.75 in.)



Ordering Information



Model Number	Description	Box Weight
OR4x-x	Optical Receiver	3 kg / 7 lb

Optical Features

Output Wavelength	1200 ~ 1600 nm
Optical Input Range	-22 ~ 0 dBm
Optic Connector Type	Std: SC/APC or Option: FC/APC

RF Features

RF Bandwidth	5 ~ 200 MHz
Adjustable Output Level Attenuation	0 ~ -20 dB
Connector Type	"F" type

**Standard Warranty: Three Years

© Copyright 2012 Taikan Company Inc. All rights reserved. This document is for information only. Features and specifications are subject to change without notice. v101413

919 E. 29th St. Lawrence, KS USA 66046 // Phone: 1-800-255-0247 // Fax: 785-841-9512 // sales@taikan.com // www.taikan.com